

Dual roller blinds

Inside fit

**bargain
blinds**


Getting started

Being careful not to damage the blind or chain when cutting through the packaging, unpack the blind and check all parts are included:

- 1 pair of slimline double brackets
- 4 x screws
- 4 x ball stops
- 2 x child safety tensioners with screw

Tools required:


- Pencil
- Tape measure
- Electric screwdriver
- #2 square drive



Step 1

1 x left hand double bracket
2 x screws


Fix the left hand double bracket inside the window frame in the top left hand corner of the window using two of the screws provided.



Step 2

1 x right hand double bracket
2 x screws


Repeat step 2 on the right side of the window measuring the same distance back from the front of the frame.



Step 3

With clean hands, lift the back / bottom blind up to the window with the controls on the side selected when ordering.


Place the spring pin-end into the bracket first (the opposite end to the chain).



Step 4




Applying pressure toward the pin end (to depress the pin), move the chain end of the blind into the bracket.

Pull down gently until the hooks at the end of the blind set into the bracket.



Step 5

Repeat step 4 with the front / top blind, being careful to set the chain into the chain diverter as shown.



Step 6

Remove the rubber band from the chains to operate the blinds.


Step 7

4 x ball stops

Attaching ball stops ensures the blind is not wound up or down too far, preventing damage.

Roll the blind to the top of its range, note the position on the chain and attach ball stop.

Roll the blind to the bottom of its range, note the position on the chain and attach ball stop.



Step 8

2 x child safety tensioners with screws

Place the tensioners over the chain and let hang to determine where to position the tensioners.

Using the screws provided, secure the child safety tensioners to the inside of the window frame.

Tip: Don't pull the chain completely tight, leave a little bit of give to make operating the blind easier.