

Curtain installation

Reverse pleat

bargain
blinds and
curtains

Getting started

Be careful not to damage the curtain when removing the packaging. Unpack the curtain and check the following parts are included:





- Curtain/s
- Metal pin hooks
- Glides are supplied with tracks and rods.

Tools required:

- Tape measure

Curtain construction:

Curtains with the reverse pleat heading style are made without tape or stiffening rods and hung using the metal pin hooks provided, which are inserted in the back of the curtain, on the side of each pleat.



Step 1

Decide how far above the hole in the glide you want your curtains to sit. If hanging under a rod, the curtains will likely sit 10mm above the hole (a).

If using a track, the curtains will likely sit 50mm above (b).

Step 3

Lift the curtain off the ground and begin hanging by inserting the first hook into the endcap of the curtain track. Continue by inserting the next hook into the first glide and so on until your curtain is hanging off the track or rod.

If hanging a pair of curtains, repeat this step but from the other side, working inwards to the centre.

Tip: We recommend resting the curtain over your shoulder as you do this so it doesn't pull heavily on the track/rod before it is fully installed. You may need someone to help you.



Step 2

Insert the point of the pin hook a further 33mm down the header tape than the distance you want the drape above the hole. E.g. if installing the drape 10mm above the hole for a rod, insert the pin 43mm down from the top of the tape (10mm + 33mm).

If 50mm above, insert the hook 83mm below the top (50mm + 33mm).

Place the first hook into the edge of the flap at the end of the curtain and remaining hooks in to the side of the pleat (a).

Be careful **not** to protrude through the front of the curtain (b).



Step 4

To remove any excess glides, grip the bottom of the glide and push it up while also pushing backwards. Reverse this step to add glides where you need them.

Tip: If the metal hooks pop out of their glides, squeeze them closed a bit more.

